

## JETEX 205 Speciality Carbon Black

### Product Description

**JETEX 205** is a high-performance speciality black designed to provide superior UV protection along with good covering power in plastics applications. With low grit, ash and excellent dispersion characteristics, it offers longer screen life and smooth surface finish. JETEX 205 is commonly used where good weathering resistance and opacity are required.

### Product Features

- When properly dispersed, enables mechanical durability by protecting the polymer against UV damage
- Low ash and grit to provide excellent surface aesthetics
- Designed for good dispersion

### Applications

- Agricultural films including thin films where mechanical integrity is important
- General purpose moulding

### Typical Values

	ASTM Test Method	Units	Typical Values
I <sub>2</sub> No.	D-1510	(g/kg)	125
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	114
Tint (ITRB #3)	D-3265	%	116
S.R # 325	D-1514	ppm	<40
Heating Loss (as packed)	D-1509	%	<1
Fines	D-1508	%	<15 (PB) <10 (JB)
Ash	D-1506	%	0.2 <sup>®</sup>

### Packaging

Bag Packaging Options: 25 kg polyethylene lined paper bags

Bulk Packaging Options: Flexible intermediate bulk containers (FIBC) depending on region

## Disclaimer

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

RAJSHILA®