

KOHLNSTOFF® COLORX 22

Speciality Carbon Black

Product Description

COLORX 22 is a general purpose high structure powder black offers high jetness and better disperse ability than the similar type of carbon black grades. It is suitable for printing inks, aqueous newspaper inks, adhesive, sealants & PVC compounding applications.

Application

- Structural adhesives in transportation manufacturing applications such as windshield bonding.
- Used for pigmentation in coating application including industrial, decorative and powder coating.
- Suitable for Aqueous Flexo ink, Plastics, Master batch.

Test	ASTM Test Method	Units	Typical Value
BET Surface Area	D-6556	(m ² /gm)	112
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	115
Tint Strength	D-3265	%	112
Sieve Residue # 325	D-1514	ppm	<50
Heating Loss (as packed)	D-1509	%	<3

Packaging

- Product Form: Powder
- Regional Availability: Global
- Bag Packaging Options: 20 kg paper bags

Disclaimer:

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.