

KOHLNSTOFF® JETEX 114

Speciality Carbon Black

Product Description

JETEX 114 is a low structure high surface area black that has been specifically formulated with a high level of color intensity in mind, making it ideal for applications where high gloss and a blue undertone is desired. It's easy-to-disperse properties make it easy to process in even at higher loading. Designed to give good gloss in lithographic gloss inks and other liquid inks requiring high gloss and lower viscosity. Also available in powder form as COLORX 14.

Application

- Different types of ink application Letter press, Offset set inks system.
- Liquid Inks Flexo & Gravure both solvent & waster based systems.

Test	ASTM Test Method	Units	Typical Value
BET Surface Area	D-6556	(m ² /gm)	103
Oil Absorption No. (OAN)	D-2414	(cc/100 g)	54
Tint Strength	D-3265	%	125
Sieve Residue # 325	D-1514	ppm	<50
Heating Loss (as packed)	D-1509	%	<3

Packaging

- Product Form: Available both in Powder & Bead form.
- Regional Availability: Global
- Bag Packaging Options: 20 kg paper bags

Disclaimer:

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.